

Package: rsf (via r-universe)

September 15, 2024

Type Package

Title Report of Statistical Findings in 'bookdown'

Version 0.3.0

Description A report of statistical findings (RSF) project template is generated using a 'bookdown' format. 'YAML' fields can be further customized. Additional helper functions provide extra features to the RSF.

License MIT + file LICENSE

URL <https://github.com/dchiu911/rsf/>, <https://dchiu911.github.io/rsf/>

BugReports <https://github.com/dchiu911/rsf/issues>

Imports bookdown, gert, here, knitr, magrittr, renv, rlang, usethis, yaml, ymlthis

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.1

Repository <https://dchiu911.r-universe.dev>

RemoteUrl <https://github.com/dchiu911/rsf>

RemoteRef HEAD

RemoteSha ca5613b3a449d65ff622e9ecb56fc4461929c32d

Contents

git_ignore_outputs	2
use_references	2
use_rsfs	3

Index	4
--------------	----------

git_ignore_outputs *Git ignore generated outputs*

Description

Add generated reports, figures, and HTML libraries to .gitignore

Usage

```
git_ignore_outputs(path = ".", figs_only = TRUE)
```

Arguments

path path of the directory containing the input files .gitignore and _bookdown.yml.
figs_only logical; if TRUE (default), only figures are git ignored.

Examples

```
wd <- tempdir()
savedir <- setwd(wd)
file.copy(list.files(system.file("extdata", package = "rsf"),
                      full.names = TRUE, all.files = TRUE, no.. = TRUE), ".")
file.rename("gitignore", ".gitignore")
git_ignore_outputs(figs_only = FALSE)
setwd(savedir)
```

use_references *Use references*

Description

Add a References section at the end of the RSF.

Usage

```
use_references(path = ".", number = 99)
```

Arguments

path path of the directory containing the input files index.Rmd, _output.yml, preamble.tex.
number number prepended to references Rmd source file.

Examples

```
wd <- tempdir()
savedir <- setwd(wd)
file.copy(list.files(system.file("extdata", package = "rsf"),
                        full.names = TRUE), ".")
use_references(number = 4)
setwd(savedir)
```

use_rsf

Use RSF project template

Description

Opens a new R project using the RSF template. Intended for use in RStudio, not interactively.

Usage

```
use_rsf(path, ...)
```

Arguments

path	project path
...	project configurations supported: <ul style="list-style-type: none">• output_dir in <code>_bookdown.yml</code> https://bookdown.org/yihui/bookdown/configuration.html• initialize git repo via <code>gert::git_init()</code>• initialize renv via <code>renv::init()</code>

Details

This function is called when the user selects File > New Project > New Directory > Report of Statistical Findings using bookdown. The directory name and output directory can be specified.

Index

`gert::git_init()`, 3
`git_ignore_outputs`, 2

`renv::init()`, 3

`use_references`, 2
`use_rsf`, 3